SOLIDOR SPECIFICATION STANDARDS

| SOLIDO | R STANDARD DOORS OPEN IN ONLY |
|-------------|--|
| FRAME | Krommerling C70 / O70 or Deceuninck |
| SLAB | Solidor 48mm Slab |
| COLOUR | All Solidor Colours |
| GLASS | 6.8 Laminated Glass External Pane |
| CASSETTES | Trysis Glazing System |
| LOCK | Avantis, Key-Windup, Heritage, Trulock, AV2 |
| HINGES | Dorpro 2D Hinges |
| LETTERPLATE | TS008* |
| HANDLE | Any Handle |
| CYLINDER | Any 3 Star Cylinder Key/Key or Thumbturn (Ultion) ** |
| THRESHOLD | AM3 (not70) Std and Low PVC |

| SOLIDOR STABLE DOORS OPEN IN ONLY | | |
|-----------------------------------|--|--|
| FRAME | Krommerling C70 / O70 | |
| SLAB | Solidor 48mm Slab | |
| COLOUR | All Solidor Colours | |
| GLASS | 6.8 Laminated Glass External Pane | |
| CASSETTES | Trysis Glazing System | |
| LOCK | Stable Door Lock | |
| HINGES | Dorpro 2D Hinges | |
| LETTERPLATE | None | |
| HANDLE | Any Handle | |
| CYLINDER | Any 3 Star Cylinder Key/Key or Thumbturn (Ultion) ** | |
| THRESHOLD | AM3 (not70) Std and Low PVC | |
| | | |

| SOLIDOR FRENCH DOORS OPEN IN ONLY | | |
|-----------------------------------|--|--|
| FRAME | Krommerling C70 / O70 | |
| SLAB | Solidor 48mm Slab | |
| COLOUR | All Solidor Colours | |
| GLASS | 6.8 Laminated Glass External Pane | |
| CASSETTES | Trysis Glazing System | |
| LOCK | French Door Locks | |
| HINGES | Dorpro 2D Hinges | |
| LETTERPLATE | TS008* | |
| HANDLE | Any Handle | |
| CYLINDER | Any 3 Star Cylinder Key/Key or Thumbturn (Ultion) ** | |
| THRESHOLD | AM3 (not70) Std and Low PVC | |
| | | |

NOTES

- * If a letterplate is selected it must be fitted in the midrail.
- ** If the door is having a thumbturn it must have a security cowl fitted to the letterplate to comply with Doc Q and PAS24-2012, for PAS24-2016 / SBD a TS008 letterplate has to be fitted.

If we are supplying a door to comply with Doc Q or Secured By Design and the door is a front door then it must have the following:
(1) A spyhole fitted unless (a) the door has clear glass, (b) there is a window adjacent to the door that has clear glass.
(2) A door guard must be supplied unless the door is going to be supplied into a warden controlled area.

PLEASE NOTE ALL INFORMATION ABOVE IS CORRECT AT THE TIME OF PUBLISH. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE, DUE TO SUPPLY CHAIN DEMAND.